

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number
WO 03/088229 A1

(51) International Patent Classification⁷: **G11B 7/09**

Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **SINGH, Gurdev** [SG/SG]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(21) International Application Number: **PCT/IB03/01447**

(22) International Filing Date: **9 April 2003 (09.04.2003)**

(74) Agent: **DEGUELLE, Wilhelmus, H., G.**; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(25) Filing Language: **English**

(26) Publication Language: **English**

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(30) Priority Data:
PCT/SG02/00075 **17 April 2002 (17.04.2002)** **SG**

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(71) Applicant (*for all designated States except US*): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **YAK, Aik, S.** [SG/SG]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **WON, Pei, C.** [MY/SG]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **LIM, Tuck, L.** [SG/SG];

[Continued on next page]

(54) Title: **OPTICAL PICKUP**



(57) Abstract: An optical disc drive (1) comprises an optical pickup (3) with a 4-quadrant photo-detector (20); an objective lens (14) mounted displaceably with respect to the photo-detector (20); an optical displacement actuator (30) for displacing the objective lens (14); and a servo controller (70) for controlling the focus actuator (30). The controller (70) receives respective detector signals (S1, S2, S3, S4) from the photo-detector (20). The controller (70) is adapted to process these detector signals to produce a focal error signal (FE) which is zero if these signals all have identical magnitude. The controller (70) is further adapted to subtract/add an offset parameter (ϕ_{off}) from/to said focal error signal (FE), and to provide the difference/sum as a control output signal.